



# OVATION<sup>®</sup>

FOR THE PROS. BY THE PROS.



## NOW AT LOWE'S, PERFECT FOR PROS.

A premium Paint and Primer in One with smooth application and durability. Its smooth-glide formula provides great coverage with minimal brush and roller marks. This ultra durable Paint and Primer in One will deliver exceptional results for your next job.

## INTERIOR

### KEY BENEFITS

- Premium Paint and Primer in One
- Ultra smooth application with minimal brush & roller marks
- Extremely durable coating for professional results
- Great coverage for a uniform finish
- Formulated to be extremely scrubbable – stands up to repeated washing and scrubbing
- Mildew-resistant coating

Available at



## EXTERIOR

### KEY BENEFITS

- Premium Paint and Primer in One
- Low temperature application to 35°F extends painting season
- 100% acrylic formula for excellent protection from cracking, peeling and blistering
- Great coverage and durability for long lasting finish
- Ultra smooth application with minimal brush & roller marks
- Mildew-resistant coating

© 2015 The Sherwin-Williams Company. HGTV and HGTV HOME are trademarks and registered trademarks of Scripps Networks, LLC in the United States and/or other countries. Used under license. LOWE'S and Gable Mansard Design are registered trademarks of LF, LLC. All are used with permission.

Please contact Customer Service for your local sales representative: 1-855-330-4753.

## WHERE TO USE

**Interior:** Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

**Exterior:** Properly prepared exterior surfaces of wood, hardboard, aluminum siding, vinyl siding, masonry, brick, stucco, cement composition panels and metal. Not for use on floors.

## COVERAGE

**Interior:** Up to 400 sq ft/gal depending on surface texture and porosity.

**Exterior:** Up to 250-400 sq ft/gal depending on surface texture and porosity.

## SURFACE PREPARATION

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with Ovation® Interior Paint & Primer.

## APPLICATION

**Interior:** Apply product when surface, air and product temperatures are between 50-90°F. Stir paint thoroughly. Inter-mix containers for uniformity. Apply with a premium-quality 1/4" - 3/4" nap synthetic roller cover, nylon/polyester brush or an airless sprayer (2000 psi, .017"-.021" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Cross-roll to spread the paint. Finish with light roller strokes in one direction, to ensure even coverage on the surface. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

**Exterior:** When air temperature is 35°F, substrates may be colder; prior to painting, check to be sure the air, surface and material temperatures are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours. Do not apply when air or surface temperatures may drop below 35°F within 48 hours. On large expanses of metal siding, the air, surface and material temperatures must be 50°F or higher. No reduction necessary. Apply with a nylon/polyester brush, 3/8" - 3/4" nap synthetic roller cover, or airless spray (2000 psi, .015" - .019" tip).

## CLEAN-UP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's instructions when using mineral spirits. Do not pour unused contents down the drain. Consult with local authorities for proper methods of disposal and recycling.

## RATE AND REVIEW

Please visit our website [Painton.com](http://Painton.com) to rate and review the products.

	FLAT	EGGSHELL	SATIN	SEMI-GLOSS
<b>Quarts - Interior</b>				
Extra White	636645	636648	756338	636651
Deep	636654	636657	756341	636660
Ultra Deep	636663	636665	756344	636667
<b>Gallons - Interior</b>				
Extra White	636646	636649	756339	636652
Deep	636655	636658	756342	636661
Ultra Deep	636664	636666	756345	636668
White Ceiling	636643			
<b>Five Gallon Pails - Interior</b>				
Extra White	636647	636650	756340	636653
Deep	636656	636659	756343	636662
White Ceiling	636642			
<b>Quarts - Exterior</b>				
Extra White	636333		636352	636355
Deep	636334		636337	636340
Ultra Deep	636343		636347	636349
<b>Gallons - Exterior</b>				
Extra White	636344		636353	636356
Deep	636335		636338	636341
Ultra Deep	636345		636348	636350
<b>Five Gallon Pails - Exterior</b>				
Extra White	636351		636354	636357
Deep	636336		636339	636342
Ultra Deep	636346			

	HIGH-GLOSS
<b>Quarts - Int/Ext</b>	
Extra White	636702
Deep	636706
Ultra Deep	636708
Black	636701
<b>Gallons - Int/Ext</b>	
Extra White	636703
Deep	636705
Ultra Deep	636707
Black	636700
<b>Five Gallon Pails - Int/Ext</b>	
Extra White	636704



Available at

